



RoofTec[®]
SYSTEMS



ConTec

Use to remove grease, oil and grime from concrete and bricks for superior cleaning performance.

1 US Gallon

Professional Use Only
Formulated with a restoration-strength blend of high-alkaline solvents and surfactants, this multi-purpose cleaner will cut through the toughest grease, oil and grime on concrete driveways, walls, and bricks.

Use Instructions:
Before use, test in an inconspicuous area. If surface has been previously cleaned with a product containing bleach, then rinse well before using this product. Not recommended for use on wood, aluminum, carpets, fabrics or other delicate surfaces. Avoid contact with solar panels including the sides, underside, wiring harnesses and/or cables. Use with caution on painted surfaces, plastics and "no-wax" resilient floors.

Dilution:
Do not use with bleach.
Do not use in RoofTec Systems equipment.

Apply with a pump-up sprayer using the following dilution.
Light cleaning: Mix 1-4 oz. per gal. of hot water.
General cleaning: Mix 4-8 oz. per gal. of hot water.
Heavy-duty cleaning: Mix up to 32 oz. with hot water to make one gallon.
pH: 11.4 - 11.8 ready to use

NOTICE: Product must be stored at room temperature (59°F - 86°F / 15°C - 30°C). Keep in sealed container when not in use. Product is not warranted if used for repack, improperly stored, or used in a manner not consistent with manufacturer's instructions.

CAUTION: Use product only in well-ventilated area
⚠ WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Solo para uso profesional
Este limpiador multiusos, formulado con una mezcla de disolventes y surfactantes altamente alcalinos con resistencia a la restauración, cortará

la grasa, el aceite y la suciedad más resistentes en entradas de hormigón, paredes y ladrillos.

Instrucciones de uso:
Antes de su uso, realice la prueba en un área poco visible. Si la superficie se ha limpiado previamente con un producto que contenga lejía, enjuáguela bien antes de utilizar este producto. No se recomienda su uso en madera, aluminio, alfombras, telas u otras superficies delicadas. Evite el contacto con paneles solares, incluidos los laterales, la parte inferior, los arneses de cables y/o los cables. Utilice con precaución en superficies pintadas, plásticos y suelos resistentes sin cera.

Disolución:
No utilizar con lejía.
No utilizar en equipos RoofTec Systems.

Aplicar con un rociador de bomba utilizando la siguiente disolución.
Limpieza ligera: Mezcle 1-4 onzas por galón de agua caliente.
Limpieza general: Mezcle 4-8 onzas por galón de agua caliente.
Limpieza de alta resistencia: Mezcle hasta 32 onzas con agua caliente para hacer un galón.
pH: 11.4 - 11.8 listo para usar

AVISO: El producto debe almacenarse a temperatura ambiente (entre 15 °C y 30 °C / 59 °F y 86 °F). Conservar en un recipiente sellado cuando no se utilice. El producto no está garantizado si se usa para reenvasar, se almacena de forma incorrecta o se usa de una manera que no cumpla con las instrucciones del fabricante.

ATENCIÓN: Use el producto solo en zonas bien ventiladas.
Contiene: agua (CAS 7732-18-5), 2-(2-butoxi)etanol (CAS 112-34-5), NTA trisódico (CAS 5064-31-3), metasilicato de sodio (CAS 6834-92-0), trisódico fosfato anhidro (CAS 7601-54-9), sulfonato de sodio xileno, alcoholes etoxilados, C9-C11, etilenglicol monobutil éter, hidrógeno fosfato dipotásico, EDTA tetrasódico, sulfato de sodio, dihidrógeno fosfato de potasio, hidróxido de sodio, azul ácido 145, 1,4-dioxano, óxido de etileno

⚠ ADVERTENCIA: Este producto puede exponerlo a Óxido de etileno, que según el estado de California provoca cáncer, anomalías congénitas u otros perjuicios reproductivos. Para obtener más información, visite www.P65Warnings.ca.gov

ConTec
DANGER
Causes severe skin burns and eye damage.



Prevention: Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. **If on skin (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **If inhaled:** Remove person to fresh air and keep comfortable for breathing. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

If any condition(s) persist: Get medical advice/attention. More detailed First Aid measures may be found in Section 4 of the SDS.

Storage: Store locked up.
Disposal: Dispose of contents in accordance with local/regional/national/international regulations.

Contains: water (CAS 7732-18-5), 2-(2-butoxi)etanol (CAS 112-34-5), trisodium NTA (CAS 5064-31-3), sodium metasilicate (CAS 6834-92-0), trisodium phosphate anhydrous (CAS 7601-54-9), sodium xylene sulfonate, ethoxylated alcohols, C9-C11, ethylene glycol monobutyl ether, dipotassium hydrogen phosphate, tetrasodium EDTA, sodium sulfate, potassium dihydrogen phosphate, sodium hydroxide, acid blue 145, 1,4-dioxane, ethylene oxide

READ SDS at LegendBrandsCleaning.com
Net Contents : 1 US Gallon
Legend Brands USA 15180 Josh Wilson Road, Burlington, WA 98233 800-932-3030

Made in U.S.A
INFOTRAC: 1-800-535-5053 (North America)
125177A

